

# Seles

## ZAŠTITE

27010 - 1 KG

27011 - 3 KG

27012 - 5 KG

## Zaštita podvozja bitumen

CODE

NAME



F Highly flammable



N Dangerous for the environment

### PRODUCT

*Zaštita podvozja bitumen* is a brushable, anti gravel and anti corrosion coating with sound deadening properties based on bitumen. After drying remains waterproof elastic coating that protects against various climates and gravel.

### APPLICATION:

Stir well before use. The surfaces to be treated must be clean, dry, rust-, dust- and grease free. *Zaštita podvozja bitumen* can be applied without dripping in very thick layers by brush or spatula. Depending on the application the product can be thinned with a solvent. If thicker layers are wanted it is to be recommended to dry the layers in between.

Product	Zaštita podvozja bitumen 27010, 27011, 27012
V.O.C.	V.O.C. category and limit value: B(e), 840 g/l. This products contain at most 325,9 g/l
Colour	Black
Overpaintable	NO
Dry to touch	90 min
Completely dried	10 h
Storage	The product may not be stored under +10°C and above +30°C. The packaging must be protected from direct sunlight and heat. Cool and moisture free stored the product is tenable for a minimum 2 years in the unopened original packaging.
Packaging	27010 – 1 kg, 27011 – 3 kg, 27012 – 5 kg

### SAFETY MEASURES

Look at Technical data sheet.

### ADR CLACIFICATION

Look at Technical data sheet

RESPONSIBILITY STATEMENT

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy. THIS PRODUCT IS FOR THE PROFESSIONAL PAINTING BY QUALIFIED PERSONNEL