

27020 – 1 L

## Zaštita podvozja bitumen

CODE

NAME



F Highly flammable



N Dangerous for the environment

### PRODUCT

*Zaštita podvozja bitumen* is a durable anti corrosion coating based on bitumen. The product has excellent sound deadening effects and offers a durable protection to the chassis of for instance cars, trucks and coaches. After drying remains a tough, adhesive film resistant against various climates and gravel.

### APPLICATION:

Shake before use. The surfaces to be treated must be clean, dry, rust free, dust free and grease free. *Zaštita podvozja bitumen* can be applied with light airless equipment, but also by means of an air-line fed gun with an air-pressure of 3-6 bar. Optimum spraying distance is about 30 cm. Depending on the application the product can be thinned with a solvent. Contaminated surfaces and filthy equipment can be simply cleaned in "fresh" condition with solvents.

PRODUCT	Zaštita podvozja bitumen 27020
V.O.C.	V.O.C. category and limit value: B(e), 840 g/l. This products contain at most 427,0 g/l
Colour	Black
Overpaintable	NO
Dry to touch	150 min
Completely dried	5 h
Storage	The product may not be stored under +10°C and above +30°C the packaging must be protected from direct sunlight and heat. Cool and moisture free stored the product is tenable for a minimum of 2 years in the unopened original packaging.
Packaging	27020 – 1 L

### SAFETY MEASURES

Look at Technical data sheet.

### ADR CLACIFICATION

Look at Technical data sheet

### RESPONSIBILITY STATEMENT

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy. THIS PRODUCT IS FOR THE PROFESSIONAL PAINTING BY QUALIFIED PERSONNEL